

Anonymous UUID: BC2E6C75-5C04-0FD7-2940-849B0908F07B

Sun Apr 16 18:03:53 2023

*** Panic Report ***

Machine-check capabilities: 0x00000000000001c09

family: 6 model: 44 stepping: 2 microcode: 31

signature: 0x206c2

Intel(R) Xeon(R) CPU X5690 @ 3.47GHz

9 error-reporting banks

Processor 0: IA32_MCG_STATUS: 0x0000000000000004

IA32_MC8_STATUS(0x421): 0xfe0001800001009f

IA32_MC8_ADDR(0x422): 0x00000000106b4000

IA32_MC8_MISC(0x423): 0x24a65b7300044000

Processor 1: IA32_MCG_STATUS: 0x0000000000000004

IA32_MC8_STATUS(0x421): 0xfe0001800001009f

IA32_MC8_ADDR(0x422): 0x00000000106b4000

IA32_MC8_MISC(0x423): 0x24a65b7300044000

Processor 2: IA32_MCG_STATUS: 0x0000000000000004

IA32_MC8_STATUS(0x421): 0xfe0001800001009f

IA32_MC8_ADDR(0x422): 0x00000000106b4000

IA32_MC8_MISC(0x423): 0x24a65b7300044000

Processor 3: IA32_MCG_STATUS: 0x0000000000000004

IA32_MC8_STATUS(0x421): 0xfe0001800001009f

IA32_MC8_ADDR(0x422): 0x00000000106b4000

IA32_MC8_MISC(0x423): 0x24a65b7300044000

Processor 4: IA32_MCG_STATUS: 0x0000000000000004

IA32_MC8_STATUS(0x421): 0xfe0001800001009f

IA32_MC8_ADDR(0x422): 0x00000000106b4000

IA32_MC8_MISC(0x423): 0x24a65b7300044000

Processor 5: IA32_MCG_STATUS: 0x0000000000000004

IA32_MC8_STATUS(0x421): 0xfe0001800001009f

IA32_MC8_ADDR(0x422): 0x00000000106b4000

IA32_MC8_MISC(0x423): 0x24a65b7300044000

Processor 6: IA32_MCG_STATUS: 0x0000000000000004

IA32_MC8_STATUS(0x421): 0xfe0001800001009f

IA32_MC8_ADDR(0x422): 0x00000000106b4000

IA32_MC8_MISC(0x423): 0x24a65b7300044000

Processor 7: IA32_MCG_STATUS: 0x0000000000000004

IA32_MC8_STATUS(0x421): 0xfe0001800001009f

IA32_MC8_ADDR(0x422): 0x00000000106b4000

IA32_MC8_MISC(0x423): 0x24a65b7300044000

Processor 8: IA32_MCG_STATUS: 0x0000000000000004

IA32_MC8_STATUS(0x421): 0xfe0001800001009f

IA32_MC8_ADDR(0x422): 0x00000000106b4000

IA32_MC8_MISC(0x423): 0x24a65b7300044000

Processor 9: IA32_MCG_STATUS: 0x0000000000000004

IA32_MC8_STATUS(0x421): 0xfe0001800001009f

IA32_MC8_ADDR(0x422): 0x00000000106b4000

IA32_MC8_MISC(0x423): 0x24a65b7300044000

Processor 10: IA32_MCG_STATUS: 0x0000000000000004
IA32_MC8_STATUS(0x421): 0xfe0001800001009f
IA32_MC8_ADDR(0x422): 0x00000000106b4000
IA32_MC8_MISC(0x423): 0x24a65b7300044000
Processor 11: IA32_MCG_STATUS: 0x0000000000000004
IA32_MC8_STATUS(0x421): 0xfe0001800001009f
IA32_MC8_ADDR(0x422): 0x00000000106b4000
IA32_MC8_MISC(0x423): 0x24a65b7300044000
mp_kdp_enter() timed-out on cpu 12, NMI-ing
mp_kdp_enter() NMI pending on cpus: 0 1 2 3 4 5 6 7 8 9 10 11 13 14 15 16 17 18
19 20 21 22 23
mp_kdp_enter() timed-out during locked wait after NMI;expected 24 acks but
received 1 after 37442141 loops in 1728999779 ticks
panic(cpu 12 caller 0xfffff8003edb5da): "Machine Check at 0xfffff8003dcabb4,
registers:\n" "CR0: 0x000000008001003b, CR2: 0xfffff8559179000, CR3:
0x0000000008684000, CR4: 0x00000000000226e0\n" "RAX:
0x0000000000000000, RBX: 0x0101010101010101, RCX: 0x0000000000000000,
RDX: 0x0000000000000000\n" "RSP: 0xfffff855973bed0, RBP: 0xfffff855973bf30,
RSI: 0xffffffff000fff, RDI: 0xfffff805f926090\n" "R8: 0x0f0f0f0f0f0f0f0f, R9:
0x3333333333333333, R10: 0x5555555555555555, R11: 0x0000000000000000\n"
"R12: 0xfffff805ffe4000, R13: 0xfffff80046a03d0, R14: 0xfffff805f926000, R15:
0xfffff853913d000\n" "RFL: 0x0000000000000046, RIP: 0xfffff8003dcabb4, CS:
0x0000000000000008, SS: 0x0000000000000000\n" "Error code:
0x0000000000000000\n" @/BuildRoot/Library/Caches/com.apple.xbs/Sources/xnu/
xnu-4903.278.70/osfmk/i386/trap_native.c:168
Backtrace (CPU 12), Frame : Return Address
0xfffff8003b57330 : 0xfffff8003dad5cd
0xfffff8003b57380 : 0xfffff8003ee9245
0xfffff8003b573c0 : 0xfffff8003eda97a
0xfffff8003b57430 : 0xfffff8003d5a9d0
0xfffff8003b57450 : 0xfffff8003dacfe7
0xfffff8003b57570 : 0xfffff8003dace33
0xfffff8003b575e0 : 0xfffff8003edb5da
0xfffff8003b576d0 : 0xfffff8003d5b22f
0xfffff855973bf30 : 0xfffff8003dcf2de
0xfffff855973bf80 : 0xfffff8003dcf3f0
0xfffff855973bfa0 : 0xfffff8003d5a0ce

BSD process name corresponding to current thread: kernel_task

Mac OS version:
Not yet set

Kernel version:
Darwin Kernel Version 18.7.0: Tue Jun 22 19:37:08 PDT 2021; root:xnu-
4903.278.70~1/RELEASE_X86_64
Kernel UUID: 041B6A6D-CD16-36FA-88B9-E32FF46EF89F
Kernel slide: 0x0000000003a00000
Kernel text base: 0xfffff8003c00000
__HIB text base: 0xfffff8003b00000

System model name: MacPro5,1 (Mac-F221BEC8)

System uptime in nanoseconds: 3168795764

last loaded kext at 2146360848: com.apple.driver.AppleHIDKeyboard 208 (addr 0xfffff7f86f6f000, size 45056)

loaded kexts:

com.metakine.handsoff.driver 3.1.4
com.apple.driver.AppleFileSystemDriver 3.0.1
com.apple.driver.AppleVirtIO 2.1.3
com.apple.filesystems.hfs.kext 407.200.4
com.apple.AppleFSCompression.AppleFSCompressionTypeDataless 1.0.0d1
com.apple.BootCache 40
com.apple.AppleFSCompression.AppleFSCompressionTypeZlib 1.0.0
com.apple.AppleSystemPolicy 1.0
com.apple.driver.AppleFWOHCI 5.6.0
com.apple.driver.Intel82574LEthernet 2.7.2
com.apple.driver.AirPort.Brcm4331 800.21.31
com.apple.driver.AppleAHCIPort 329.260.5
com.apple.private.KextAudit 1.0
com.apple.driver.AppleRTC 2.0
com.apple.driver.AppleHPET 1.8
com.apple.driver.AppleACPIButtons 6.1
com.apple.driver.AppleSMBIOS 2.1
com.apple.driver.AppleACPIEC 6.1
com.apple.driver.AppleAPIC 1.7
com.apple.driver.AppleIntelCPUPowerManagementClient 220.0.0
com.apple.nke.applicationfirewall 202
com.apple.security.TMSafetyNet 8
com.apple.driver.AppleIntelCPUPowerManagement 220.0.0
com.apple.driver.AppleHIDKeyboard 208
com.apple.driver.AppleUSBHIDMouse 192
com.apple.iokit.IOUSBHIDDriver 900.4.2
com.apple.driver.AppleHIDMouse 192
com.apple.driver.AppleUSBAudio 315.6
com.apple.driver.usb.IOUSBHostHIDDevice 1.2
com.apple.iokit.IOAudioFamily 206.5
com.apple.vecLib.kext 1.2.0
com.apple.driver.usb.cdc 5.0.0
com.apple.driver.usb.networking 5.0.0
com.apple.driver.usb.AppleUSBHostCompositeDevice 1.2
com.apple.driver.usb.AppleUSBHub 1.2
com.apple.iokit.IOSerialFamily 11
com.apple.filesystems.hfs.encodings.kext 1
com.apple.iokit.IOFireWireFamily 4.7.3
com.apple.iokit.IO80211Family 1200.12.2
com.apple.driver.corecapture 1.0.4
com.apple.driver.AppleUSBMergeNub 900.4.2
com.apple.iokit.IOAHCIFamily 288
com.apple.driver.usb.AppleUSBXHCIPCI 1.2
com.apple.driver.usb.AppleUSBXHCI 1.2

com.apple.driver.usb.AppleUSBEHCIPCI	1.2
com.apple.driver.usb.AppleUSBHCIPCI	1.2
com.apple.driver.usb.AppleUSBHCI	1.2
com.apple.driver.usb.AppleUSBEHCI	1.2
com.apple.driver.usb.AppleUSBHostPacketFilter	1.0
com.apple.iokit.IOUSBFamily	900.4.2
com.apple.driver.AppleUSBHostMergeProperties	1.2
com.apple.driver.AppleEFINVRAM	2.1
com.apple.driver.AppleEFIRuntime	2.1
com.apple.iokit.IOSMBusFamily	1.1
com.apple.iokit.IOHIDFamily	2.0.0
com.apple.security.quarantine	3
com.apple.security.sandbox	300.0
com.apple.kext.AppleMatch	1.0.0d1
com.apple.driver.DiskImages	493.0.0
com.apple.driver.AppleFDEKeyStore	28.30
com.apple.driver.AppleEffaceableStorage	1.0
com.apple.driver.AppleKeyStore	2
com.apple.driver.AppleUSBTDM	456.260.3
com.apple.driver.AppleMobileFileIntegrity	1.0.5
com.apple.iokit.IOUSBMassStorageDriver	145.200.2
com.apple.iokit.IO SCSI Block Commands Device	408.250.3
com.apple.iokit.IO SCSI Architecture Model Family	408.250.3
com.apple.iokit.IOStorageFamily	2.1
com.apple.kext.CoreTrust	1
com.apple.driver.AppleCredentialManager	1.0
com.apple.driver.KernelRelayHost	1
com.apple.iokit.IOUSBHostFamily	1.2
com.apple.driver.usb.AppleUSBCommon	1.0
com.apple.driver.AppleBusPowerController	1.0
com.apple.driver.AppleSEPManager	1.0.1
com.apple.driver.IOSlaveProcessor	1
com.apple.iokit.IOTimeSyncFamily	740.2
com.apple.iokit.IONetworkingFamily	3.4
com.apple.iokit.IOReportFamily	47
com.apple.driver.AppleACPIPlatform	6.1
com.apple.driver.AppleSMC	3.1.9
com.apple.iokit.IOPCIFamily	2.9
com.apple.iokit.IOACPIFamily	1.4
com.apple.kec.pthread	1
com.apple.kec.corecrypto	1.0
com.apple.kec.Libm	1

EOF

Model: MacPro5,1, BootROM 144.0.0.0.0, 12 processors, 6-Core Intel Xeon, 3.46 GHz, 48 GB, SMC 1.39f11

Graphics: AMD Radeon HD 7xxx, AMD Radeon HD 7xxx, spdisplays_pcie_device, 3 GB

Memory Module: DIMM 1, 8 GB, DDR3 ECC, 1333 MHz, 0x80CE, 0x4D33393342314B37304448302D5948392020

Memory Module: DIMM 2, 8 GB, DDR3 ECC, 1333 MHz, 0x80CE, 0x4D33393342314B37304348302D5948392020
Memory Module: DIMM 3, 8 GB, DDR3 ECC, 1333 MHz, 0x80CE, 0x4D33393342314B37304448302D5948392020
Memory Module: DIMM 5, 8 GB, DDR3 ECC, 1333 MHz, 0x80CE, 0x4D33393342314B37304348302D5948392020
Memory Module: DIMM 6, 8 GB, DDR3 ECC, 1333 MHz, 0x80CE, 0x4D33393342314B37304448302D5948392020
Memory Module: DIMM 7, 8 GB, DDR3 ECC, 1333 MHz, 0x80CE, 0x4D33393342314B37304448302D5948392020
AirPort: spairport_wireless_card_type_airport_extreme (0x14E4, 0x8E), Broadcom BCM43xx 1.0 (5.106.98.102.31)
Bluetooth: Version 6.0.14d13, 3 services, 27 devices, 1 incoming serial ports
Network Service: Wi-Fi, AirPort, en2
PCI Card: AMD Radeon HD 7xxx, Display Controller, Slot-1
PCI Card: pci1002,aaa0, Audio Device, Slot-1
PCI Card: PXS3, USB eXtensible Host Controller, Slot-3
Serial ATA Device: HL-DT-ST DVD-RW GH61N
Serial ATA Device: Samsung SSD 840 EVO 500GB, 500.11 GB
Serial ATA Device: Hitachi HDE721010SLA330, 1 TB
USB Device: USB 2.0 Bus
USB Device: USB 2.0 Bus
USB Device: Keyboard Hub
USB Device: Apple Keyboard
USB Device: USB 2.0 Hub
USB Device: USB Bus
USB Device: USB Bus
USB Device: Apple Optical USB Mouse
USB Device: USB Bus
USB Device: BRCM2046 Hub
USB Device: Bluetooth USB Host Controller
USB Device: USB Bus
USB Device: USB Bus
USB Device: USB Bus
USB Device: USB 3.0 Bus
FireWire Device: built-in_hub, Up to 800 Mb/sec
Thunderbolt Bus: